

a magnet holder having a base and a second annular wall connected with said first annular wall of said magnet for fixing said magnet;
a shaft having one end mounted through said base of said magnet holder; and
a stopper for supporting and fixing the other end of said shaft,
said stopper positioned in one location within a range of possible locations to maintain a relatively low rotational inertia, said one location corresponded to the length of said magnet.

11. (Three Times Amended) A rotor-stator assembly of a stepping motor having a relatively low inertia, comprising:

a rotor; and
a stator having a plurality of coils for causing the rotation of said rotor, wherein said rotor comprises:
a magnet having a first annular wall;
a magnet holder having a base and a second annular wall connected with said first annular wall of said magnet for fixing said magnet;
a shaft having one end mounted through said base of said magnet holder; and
a stopper for supporting and fixing the other end of said shaft,
said stopper positionable along said shaft in one location within a range of possible locations to maintain a relatively low rotational inertia, said one location corresponded to the length of said magnet..

13. The rotor structure according to claim 10, wherein said magnet holder has a fixed length.

14. The rotor structure according to claim 11, wherein said magnet holder has a fixed length.

REMARKS

LAW OFFICES OF
MACPHERSON KWOK CHEN
AND HEID LLP
2402 MICHELSON DRIVE
SUITE 210
IRVINE, CA 92612
(714) 752-7040
FAX (714) 752-7049

Claims 1-4 and 6-14 are pending. Claims 1-4, 6-9 and 12 are allowed. Claims 10 and 11 have been amended. Applicant requests reconsideration and reexamination of the pending claims.